





"TYING QUALITY AND SERVICE TOGETHER!"

- Light weight and easily blown through conduit.
- Low coefficient of friction minimized duct melting.
- Offered with printed, sequentially numbered, accurate, easy-to-read markings.
- Durable print, non-fading when wet.
- Manufactured as continuous reel lengths.
- Low elongation/dimensional stability prevents surging in use.
- Custom designed and manufactured Slick-Tape® can be made to meet your needs.
- Aramid fiber Slick-Tape® is available for high temperature plenum duct applications.

POLYESTER

Product	Strength	Approx. Width	Field Reel length
64P0400	400 lb.	3/16"	1000 m.
64P1250	1,250 lb.	1/2"	1000 m.
64P1800	1,800 lb.	5/8"	1000 m.
64P2500	2,500 lb.	3/4"	1000 m.

ARAMID

Product	Strength	Approx. Width	Field Reel length
64A1250	1,250 lb.	3/8"	1000 m.
64A1800	1,800 lb.	1/2"	1000 m.
64A2500	2,500 lb.	5/8"	1000 m.

CONDUIT MEASURING TAPE

Product	Strength	Approx. Width	Field Reel length
64M0160	160 lb.	3/16"	1000 m.

All products are available plain and printed.

Custom prints and lengths are available.

Also available in a detectable version.



PH: 877-224-2673 FAX: 888-700-7012