



APP Service Power Supply

The APP is a portable non-standby power supply used to provide conditioned AC power to the load when the main power supply is being serviced. Used in conjunction with the "Alternate" connector and the "ALT/ON" switch located on the enclosure's service power inserter, power can be transferred from the main power module to the APP without interrupting the connected load. The APP90S has an internal tap that allows the unit to be set for 90/75/60VAC applications.

Specifications

Model:	APP9015S	APP9022S
Input Voltage (VAC):	120/240 ±15%	120/240 ±15%
Input Current (A):	12	16/12 max.
Input Frequency (Hz):	60	60
Output Voltage (VAC):	60/75/90 ±5%	60/75/90 ±5%
Output Current (A):	15	17 (22 at 240VAC Input)
Output Power (VA) (Continuous):	1350	1350/1650/2000
Output Current Limit:	150% of output rating	150% of output rating
Efficiency:	90% typical @ rated load	90% typical @ rated load
Agency Compliance:	—	CSA
Finish:	Flat black	Flat black
Operating Temperature Range:	-40 to 50°C (-40 to 122°F)	-40 to 50°C (-40 to 122°F)
Dimensions (in):	9H x 9.5W x 13.75D	9H x 9.5W x 14.75D
(mm):	229H x 241W x 349D	229H x 241W x 375D
Weight (lb/kg):	47/21	60/27
Cord Options:	See below	See below



APP9015S



APP9022S

APP-9015S

Kit Includes:

- 874-726-20 Line Cord Assy, 120VAC, 5-20P, APP-9015S
- 874-727-20 Line Cord Assy, 240VAC, 6-15P, APP-9015S
- 874-728-20 Output Cable Assy, Jones Connector, APP-9015S
- 874-712-20 WR KT, ADPTR, SPS JONES to SPI 25XM

APP-9022S

Kit Includes:

- 874-935-20 Line Cord Assy, 120VAC, 5-20P, APP-9022S
- 874-935-21 Line Cord Assy, 240VAC, 6-15P, APP-9022S

All Output Cables for the APP-9022S are to be ordered as separate line items. One Standard Output Cable Kit (745-223-20) is included in the price of the APP-9022S. Additional Output Cables or 30ft Cable Kits can be ordered (additional cost) as needed.

745-223-20 Y-Cables, 25A Connectors, 6', Jones, 6, APP-9022S

Kit Includes:

- 874-949-20 Y-Cables, 25A Connectors, 6', APP-9022S
- 874-949-21 Y-Cables, Jones, 6, APP-9022S
- 875-173-20 25A Adapter, Lectro to APP-9022S



874-726-20 (5-20 plug)



874-727-20 (6-15 plug)



874-728-20



875-173-20



874-935-20 (5-20 plug)



874-935-21 (6-15 plug)



874-935-22



874-949-20



874-949-21



874-949-32



874-949-33



874-949-34

For more information visit www.alpha.com

Alpha Technologies

United States
Canada

Bellingham, Washington Tel: 360 647 2360 Fax: 360 671 4936
Burnaby, British Columbia Tel: 604 430 1476 Fax: 604 430 8908

049-224-10-002 (1/06)

Alpha Technologies reserves the right to make changes to the products and information contained in this document without notice.

Copyright © 2006 Alpha Technologies. All Rights Reserved. Alpha® is a registered trademark of Alpha Technologies. member of The Alpha Group™ is a trademark of Alpha Technologies.